

MONUMENT RECORD

Corner ID: **CICr_Y21**

Section Corner

Sections 25 & 36- T07N-R01W, 2nd P.M.
Clear Creek Township, Monroe County, Indiana




PHOTO IDENTIFIED: Photo Date: 7/30/2019



Photo Orientation & Description: CICr_Y21



Photo Orientation & Description: Looking south at CICr_Y21

EXISTING SURVEY HISTORY Include as much detail and history of the corner as known at the time of perpetuation

ORIGINAL GOVERNMENT SURVEY:

Year Surveyed: 3/27/1811 By: Alexander Holmes

Where filed or recorded: F_EV01P195

Original monument: Wooden Post

Bearing Trees or Reference Monuments:

Species	Dia.	Bearing	Distance
Ironwood	6"	S 87° E	3 lks
Sugar	9"	N 24° W	18 lks

Notes: The closing corner was later set 37 lks south

SUBSEQUENT CORNER RESTORATION:

No legal survey records found

OTHER SURVEY HISTORY: Include details such as surveyor name, date, recording info, monument description, etc.

See Monument Record for Polk_A21 for details.

OTHER EVIDENCE: Describe corner location relative to nearby features and how to reach the corner location – note fences, roads, timber cutting lines, mow lines, clearings, plantings, streams, topo changes, etc.

From the gravel pull-off at the Hoosier National Forest parcel across the road from the trailer at 5368 E Stewart Road, walk north, northwest, and west along an old road bed for approximately half a mile. The corner is about 425 feet north of the old road at the bottom of a steep ravine.

MONUMENT PRESERVATION: Describe work done to preserve existing monument.

We set a five-foot t-post with a yellow Monroe County "PROTECT NEARBY SURVEY MARKER" sign 3.5 feet south of the monument and in line with the closing corner at Polk_A21.

THEORY OF LOCATION: Describe the theory of location for acceptance of this monument. Include monument origin and associated uncertainty.

We set this corner at the record distance north of the cut x in natural stone found at the closing corner. A slight difference between measured and record distances is shown on the plat because underground obstacles prevented us from setting the rebar perfectly straight.

GEODETIC COORDINATES: Northing: 1369218', Easting: 3129428'

BASIS OF GEODETIC COORDINATES: The basis of bearings is Grid North System NAD83 (2011)/Indiana West NAVD 88, Epoch 2010.0000, geoid12b_conus.db3, US Survey Feet. Tied to NSRS using the JAVAD GNSS Data Online Processing Service (DPOS) to post-process static observations collected with a Javad Triumph 2 base. Positional values of this corner were determined from static GNSS and RTK GNSS (Javad Triumph LS Rover) observation.

This document is not complete without the associated Corner Perpetuation plat and report of survey for Section 36-T7N-R1W by Rachel Oser of the Monroe County Surveyor's Office dated August 5, 2019 and recorded as Instrument Number 2019011075 in the office of the Monroe County Recorder.



OFFICE OF THE MONROE COUNTY SURVEYOR • Trohn Enright-Randolph

119 W 7th Street, Bloomington, IN 47404 • 812-349-2570 • surveyoroffice@co.monroe.in.us

Page 2 of 3

MONUMENT RECORD

Corner ID: **CICr_Y21**

Section Corner

Sections 25 & 36- T07N-R01W, 2nd P.M.
Clear Creek Township, Monroe County, Indiana

		25			30
		36			31

CERTIFICATIONS:



Date: August 5, 2019
Rachel Oser, State of Indiana
PS No.21100022



Date: August 8, 2019
Trohn Enright-Randolph
Monroe County Surveyor



Accepted by the Monroe
County Surveyor Review
Board on August 6, 2019

